

S200

Android POS Terminal

- The 1st Third-generation Android POS



Android 13



6.7" HD Display



7.2V / 3350 mAh



4G / 3G / 2G
Wi-Fi / Bluetooth




















Omni-channel
Payment



PCI PTS 6.x



SPECIFICATIONS

	Operating System	Android 13			
	Processor	Quad-core 32-bit, 2.0GHz			
	Memory	RAM-2GB LPDDR, Flash-32GB eMMC RAM-4GB LPDDR, Flash-64GB eMMC (optional)			
	Display	6.7-inch 720*1600 IPS Capacitive multi-touch screen			
	Satellite Positioning	GPS / A-GPS / GLONASS / Beidou			
	Printer	Built-in high speed thermal printer Printing speed: >80mm/s Paper roll diameter: 40mm, width: 58mm			
	Card Readers	Magnetic Card Reader MSR-ISO7810, ISO / IEC 7811 Track 1 / 2 / 3, bi-directional	Smart Card Reader EMV L1 & L2 Supports 1.8V / 3V / 5V IC card	Contactless Card Reader Mifare classic / Mifare Ultra light / Mifare DES Fire ISO 14443 A / B EMV CL1 / Mastercard Contactless / Visa payWave	
	Communications	4G / 3G / 2G Wi-Fi: IEEE 802.11 a/b/g/n/ac, 2.4Ghz/5G BT 5.1			
	Peripheral Ports	1 x SIM / 2 x PSAM / 1 x SD / 1 x Type-C 2 x SIM / 1 x PSAM / 1 x SD / 1 x Type-C (optional) 6 PIN POGO PIN			
	Camera	Front: 2MP, FF Rear: 5MP AF with auto flash & auto focus (optional: 8MP / 13MP) Supports 1D/2D code scanning			
	Fingerprint Module	Optional			
	Audio	Speaker			
	Power Supply	Input: 110-240V AC, 50Hz / 60Hz, 0.5A Output: 5V DC / 2A			
	Battery	7.2V/3350mAh			
	Physical	L x W x H (mm): 200*80*56 Weight: 680g			
	Environmental	-10°C ~ 55°C Operating Temperature -20°C ~ 70°C Storage Temperature			
	Certifications	PCI PTS 6.x EMV L1 & L2 EMV Contactless L1 Mastercard Contactless	Visa payWave American Express Discover Pure	Quics FCC CE TQM	WEEE RoHS

